



## Important Safety Instructions

- 1) Read these instructions.
- 2) Keep these instructions.
- 3) Heed all warnings.
- 4) Follow all instructions.
- 5) Do not use this apparatus near water.
- 6) Clean only with dry cloth.
- 7) Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.
- 8) Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
- 9) Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade of the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
- 10) Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
- 11) Only use the attachments/accessories specified by the manufacturer.
- 12) Use only with the cart, stand, tripod, bracket or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.
- 13) Unplug this apparatus during lightning storms or when unused for long periods of time.
- 14) Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.




1. Unpack amplifier.


Note: Follow steps 2-5 if using the mounting adapter. If not skip to step 6.




2. Attach mounting bracket to a secure pole or surface using screws or metal strapping.




3. To attach mounting bracket, remove all faceplate screws from one side. Lift faceplate and set aside.




4. Slide mounting bracket into groove on bottom of amplifier enclosure.




5. Replace faceplate and screws.



6. Select stereo, bridged or mono mode with the included jumper.



7a. In stereo mode, the left and right channels remain separate. The amp operates as a normal stereo amp.



7b. In mono mode, the left and right inputs are combined internally and fed to both channels of the amp. The left and right channels both output the summed signal.